

LOAD CHART




Complying with EN 1459 (table B) standard.

DIMENSIONS

PANORAMIC P32.6





DIM	A	B	C	D	E	F	H	M	P	R	S	Z
mm	4220	970	2720	520	3778	385	2000	995	2150	3700	4550	850

PERFORMANCE AND DIMENSIONS

The tables shown show data relative to a machine in it's base/standard configuration.
Merlo Spa reserves the right to modify or amend machines/specifications without prior notification.

PANORAMIC	P 32.6 PLUS P 32.6 TOP
WEIGHT (kg)	
Total empty weight (with fork) : 5950	
PERFORMANCE	
Maximum load (kg)	3200
Lift height (mm)	6400
Maximum forward reach (mm)	3400
Speed (Km/h)	1st gear 0 - 15 2nd gear 0 - 40
ENGINE	
Type : Deutz BF4M2012 CE74.9/2 Turbo - direct injection – water-cooled Power : 74,9 kW – (102Hp) at 2400 rpm Emission : low emission (EURO 2)	
CABIN	
In compliance with ISO 3449 (FOPS) and ISO 3471 (ROPS) standards Mechanical joystick with electro-proportional roller control of two movements	
STEERING	
Four drive/steer wheels with automatic wheel synchronisation 3 steering modes : normal, all wheel, crab,	
TRANSMISSION	
Hydrostatic with electronic control	
HYDRAULIC SYSTEM	
P 32.6 PLUS : Hydraulic system with gear pump P 32.6 TOP : Hydraulic system with Load-Sensing pump	
ELECTRICS	
12 V, 100 Ah battery complete with manual battery isolator	
CAPACITIES (litres or dm^3)	
Hydraulic system: 85 Fuel: 100 Hydrostatic oil 12 Engine oil: 8,5 Coolant: 12	
TYRES	
405/70-20 14 PR SEMI-INDUSTRIAL PROFILE (16/70-20) 405/70-24" 14 PR 405/70-24 MICHELIN XM27 405/70-24" 14 PR SEMI-INDUSTRIAL PROFILE	